

American Chemical Technologies, Inc.
485 E Van Riper Road, Fowlerville, MI 48836
Office: 517-223-0300 Fax: 517-223-1703

EMERGENCY: INFOTRAC 1-800-535-5053 24 HOURS/DAY, 7 DAYS/WEEK
THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD COMMUNICATION STANDARD)

SECTION I – PRODUCT IDENTIFICATION

Product Name: EcoLux EP #2
Chemical Name: Lubricating Grease
DOT Hazard Classification: Not applicable

SECTION II – COMPONENTS

Chemical Name	CAS#	% Wt.	Carcinogen OSHA or IARC
Lithium 12-Hydroxy Octadecanoate Sebacate Complex	68815-49-6	8-12	No
Polyalphaolefin	68037-01-4	50-80	No
Polybutene	9003-29-6	10-30	No
Zinc Alkyldithiophosphate	68649-42-3	< 1.0	No
Red Dye		< .05	No

SECTION III – PHYSICAL DATA

Boiling Point: N/A
Melting Point: 545 ° F
Freezing Point: - 10° F
Vapor Pressure: Not applicable
Specific Gravity: 0.85 @ 16°C
Appearance: Red semi-solid
Vapor Density: Not applicable
Solubility in Water: Nil

SECTION IV – FIRE AND EXPLOSION INFORMATION

Flash Point: 485 ° F (D-92 Method)
Fire Point: 500° F
Extinguishing Media: Dry chemical, CO₂, earth, sand, foam, or water fog.
Fire Fighting Procedures: Use full protective equipment including self-contained breathing apparatus. Closed containers exposed to fire may be cooled with water. Dense smoke. Water may cause frothing.

NFPA Codes: HEALTH –0 FLAMMABILITY –1 REACTIVITY –0

SECTION V – HEALTH HAZARD DATA

Effects of Acute Overexposure: None when used with good personal hygiene practices. May otherwise cause skin and eye irritation upon prolonged or repeated contact

FIRST AID:

Skin: Wash thoroughly with water for 15 minutes. Seek medical attention if irritation persists.

Eyes: Immediately flush with large quantities of water for at least 15 minutes and seek medical attention immediately.

Inhaled: Not applicable

Ingested: **DO NOT** induce vomiting and call a physician immediately.

SECTION VI- REACTIVITY DATA

Hazardous Polymerization: Will not occur

Stability: Stable

Incompatibility: Strong oxidizing agents

SECTION VIII – SPILL OR LEAK PROCEDURES

Steps to be taken in Case Material is Released or Spilled: Absorb with sand or inert material. Sweep or scoop up and remove.

Waste Disposal Method: Dispose of in accordance with all applicable federal, state, and local regulations.

SECTION VII- PROTECTIVE EQUIPMENT

Respiratory Protection: None normally required

Protective Gloves: Neoprene, Polyethylene

Eye Protection: Face shield

Other Protective Equipment: None normally required

SECTION IX – SPECIAL PRECAUTIONS

If used in applications where a mist may be generated, observe a TWA/PEL of 5 mg/m³ for mineral oil mist (OSHA and ACGIH).

SECTION X – TOXIC CHEMICALS

This product contains the following chemicals subject to the reporting of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 (40 CFR 372):

Chemical Name: Zinc Alkyldithiophosphate **CAS#:** 68649-42-3 **% By Wt.:** <1.0 %
DOT Shipping Name: Not regulated

Prepared By: Sharon L. Haiser
Revision Date: 05/12/04
Supersedes: 9/17/02

A.C.T., Inc. believes the data set forth herein is accurate as of the data hereof. We make no warranty with respect there to and expressly disclaim all liability for reliance thereon. Such data are offered solely for your consideration, investigation, and verification.